

TEMPORARY NOISE SOLUTIONS



SOUNDEX™

noise solutions for your environment

C3/4 - Technical Data Sheet

- 32.9dB Max attenuation
- Entirely constructed from fire resistant materials
- Full weather resistant construction
- No irritant materials used
- Very high noise absorption
- Independently tested to BS EN ISO 10140-2:2010; BS EN ISO 354:2003
- Velcro joining system for easy installation creating a seamless noise barrier



For more information on this product please call 0411 484 970

Email: info@temporarynoisesolutions.com.au • www.temporarynoisesolutions.com.au

TEMPORARY NOISE SOLUTIONS



The SOUNDEX™ C3/4 performance temporary noise system offers a versatile approach for creating exterior or internal acoustic attenuation barriers. It reduces the noise created by typical site plant, from small fans, portable compressors, large site generators or piling rigs by both attenuation and adsorption. They enable a dynamic and versatile approach to the noise issues experienced in today's industrial, construction and event environments.

The SOUNDEX™ acoustic curtain was designed specifically to provide a light-weight, fully waterproof, fire retardant, high attenuating acoustic barrier for surrounding site plant and other high noise emitting activities. They are very quick to install and therefore ideal for both short and long term applications.

Each fire resistant curtain can be used to create any size of enclosure to ensure optimum acoustic performance. They are constructed with eyelets positioned along the top and down both sides to enable suspension from site fencing, scaffolding, timber hoarding's and many other structures.

The curtains have a single horizontal fold line to make storage and transportation easy.

- 32.9dB Max attenuation
- Entirely constructed from fire resistant materials
- Full weatherproof construction
- No irritant materials used
- Very high noise absorption
- Independently Tested to BS EN ISO 10140-2:2010; BS EN ISO 354:2003
- Single horizontal fold line for lay-flat storage and easy palletised transportation

SOUNDEX™ C3/4 - Performance Acoustic Curtain Test Data*

Frequency Hz



50	63	80	100	125	160	200	250	315	400	500	630	800	1000	1250	1600	2000	2500	3150	4000	5000
----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------	------	------	------	------

Attenuation dB

12.8	10	9.3	13.5	12.4	15.1	18.3	18.8	18.6	21.3	22.8	23.2	23.8	22.9	22.5	23.2	25.1	27.5	29.5	31.1	32.9
------	----	-----	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Absorption

0.06	0.06	0.08	0.13	0.21	0.32	0.4	0.46	0.5	0.59	0.7	0.81	0.87	0.94	0.96	0.93	0.89	0.83	0.92	1	0.98
------	------	------	------	------	------	-----	------	-----	------	-----	------	------	------	------	------	------	------	------	---	------



SOUNDEX™ C3/4 - Performance Acoustic Curtain Fire Rating Statistics

Acoustic Vinyl Membrane	M2 / B1 / BS B-s2-d0 / NFPA701	Acoustic Core	Class 0	Acoustic Mesh Membrane	M2
-------------------------	--------------------------------	---------------	---------	------------------------	----

For more information on this product please call 0411 484 970

Email: info@temporarynoisesolutions.com.au • www.temporarynoisesolutions.com.au